



**1200 W @ 50 OHMS = ~350 V PEAK & 7 A PEAK**

**RELAYS: SPDT MADE FOR 16 AMPS AC  
 OMRON G2RL-1-E, G2R-1-E, FINDER 40-61, OR EQUIVALENT.  
 USE PREFERABLY LOW PROFILE RELAYS TO MINIMIZE INDUCTANCES (BETTER SWR).  
 COIL 24 V DC (SAME AS OTHER SSPA BOARDS & ANTENNA RELAYS)  
 OR FOR 24 V SUPPLY & 12 V RELAYS, USE A SERIAL RESISTOR (USE OHM'S LAW, IF YOU HEARD ABOUT IT)**

**BYPASS RELAYS FOR 1.2 KW HF  
 FROM 160 M TO 6 M**

DOC N°: AMATEUR RADIO  
 BY: F1FRV@SFR.FR  
 DATE: 22/01/15 REV: 0 PAGE: 1/1

**BYPASS RELAYS FOR 1.2 KW HF SSPA  
160 METERS TO 6 METERS**

DATE: 01/2015 REV: 1  
 BY: F1FRV@SFR.FR  
 DOC N°: AMATEUR RADIO

REVISION 1 WITH 60 MM INSTEAD OF ~70 MM BETWEEN CONNECTORS.

SINGLE SIDE PCB DIMENSIONS: 107.95 x 52.1 mm (4.25 x 2.05") 36 HOLES  
 PCB CAN BE PLACED INTO SCHUBERT TINY BOX 55 x 111 x 50 mm

NOTA: DUE TO HIGH RF CURRENTS ~ 7 AMPS RF BETWEEN AMPLIFIER & ANTENNA,  
 WHEN SOLDERING, PLACE MAXIMUM POSSIBLE SOLDER THICKNESS ON PCB TRACKS

